

STYLE-903

Braided from strong carbon fiber yarn , impregnated with proprietary lubricant and graphite particles, which fill voids, act as a break-in lubricant, and block leakage.

STYLE-903 used for pumps and valves in high pressure and high temperature. Handle water, steam , acids and alkalis for power stations, refineries, boiler plants etc.



Benefits: Affordable high quality all-round packing.

NOT suitable for Highly concentrated corrosive acids

SERVICE LIMITS

	Rotating	Reciprocating	Static
Pressure (bar)	25 bar	100 bar	200 bar
Shaft speed	20m/s		
Density	1.1~1.3 g/cm ³		
Temperature	-240 +450 Deg.C (+650 Deg.C with Steam)		
PH Range	0~14		

All Technical data and recommendations given are based on our experience. However , we do not undertake any liability whatsoever, All data and values have to be checked by the user, since the effectiveness of a seal can only be judged correctly by evaluating all data parameters directly on site. The stated parameters of all packing styles are approximate and may be influenced if occurring together. We suggest you contact us in the case of special applications.

120, Raj Prabha Land Mark Industrial Estate, 1st Floor, Building no. 3, Gokhivare Village, Bhojapada, Vasai (E), Dist. Thane - 401 208.

ePTFE Gaskets & Sheets • Gland Packing • Non Asbestos Gaskets & Sheets • Metallic Gaskets and other Sealing Products

Tel.: 0250 6093377 Mob-09920168285 / 09821152367 Email : admin@sealmax.net / sales@sealmax.net Web : www.sealmax.in