

# NON-METALLIC GASKET, AFM 34 CO ME®

## 3133FD10

Sealing system with optimised inner eyelet [1.4571] complies with TA Luft and VDI 2290, has high pressure stability, high tensile, pressure and shear strength and very high gas tightness. Scratch resistant, sturdy surface, easy to handle, easy to dismantle, blow-out resistant sealing system. Resistant against a large number of chemicals, does not present a health risk, FDA-conform.



### Operating data

Temperatur [min]	-50 °C
Temperatur [max]	250 °C
Pressure [max]	125 bar

### Approvals and test reports

TA Luft 2002 [VDI 24A0/2200]
Gas [DIN 30653 [ehemals VP401; HTB]]

### Flange shapes

Self-centering, Raised Face [form IBC]
Tongue and Groove [form TG]
Male-Female [form SR]
Apparatus, customized
With partition bars

This datasheet on the internet: <https://idt-gaskets.com/products/gaskets/62e954ac6c7d623ea>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 201 85511-0 · Annaberg-Buchholz: +49 3733 505-0 · München: +49 89 991883-0  
Further sealing systems and technical information can be found [idt-gaskets.com](http://idt-gaskets.com)

Last Changed 2023-12-01