

# FLEXIBLE PURE GRAPHITE TAPE, CRINCKLED, MADE FROM PURE GRAPHITE EXPANDAT WITHOUT FILLER AND BINDERS (CORRUGATED WITH GLUE STRIP)

3890BD11

- Nuclear quality 99,85% C
- Chloride content as per DIN28090-2  $\leq 20$  ppm
- Instant sealing material for valve spindles
- Thickness [mm]: 0.35; 0.5; 0.8; 1.0
- Widths of [mm]: 5 up to 60 mm



## Operating data

Temperatur	450 °C
Temperatur [min]	-269 °C
Temperatur [max]	550 °C

## Approvals and test reports

BAM oxygen

BAM oxygen (liquid)

Gas [DIN 3535-6]

FDA [Food]

EG 1935/2004

Drinking water certificate HY

## Forms of delivery

Other dimensions are available on request.

Rolle	10m
-------	-----

This datasheet on the internet: <https://idt-gaskets.com/products/accessories/629fb77ca916ca477>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 201 855110 · Annaberg-Buchholz: +49 3733 5050 · München: +49 89 9918830

Further sealing systems and technical information can be found [idt-gaskets.com](https://www.idt-gaskets.com)

Last Changed 2025-05-28