

GROOVED GASKET WITH INTEGRAL CENTERING RING, PRE-DETERMINED BREAKING POINT AND BOTH-SIDED SILVER LAYERS

6737KD20

The grooved stainless steel core [1.4828, pitch 1,0 mm] is covered on both sides with pure silver layers. The integral centering ring [machined] is additionally provided with a pre-determined breaking point, which prevents vibration breaks in the sealing area.



The combination of a high-temperature-resistant stainless steel core with silver layers enables temperature/pressure applications beyond the range of use of conventional soft sealing materials.

Operating data

Temperatur [min]	-269 °C
Temperatur [max]	600 °C
Pressure [max]	80 bar

Gasket characteristics EN 13555

Gasket Parameters 5 mm [Amtec]

https://idt-gaskets.com/download/dichtungskennwerte/28C8_294

Gasket characteristics DIN 2505 V

$K_0 \times K_d$ [N/mm]	$100 \times b_d$
k1 [mm]	$1,1 \times b_d$

Gasket characteristics DIN 28090

σ_{V0} [N/mm ²]	500
$\sigma_{VU 0,1}$ [N/mm ²]	100
m [DIN 28090]	1.1
$\sigma_{B0 300 \text{ °C}}$ [N/mm ²]	420

Gasket characteristics ASME

m [ASME]	4.25
Y [PSI]	10000

Flange shapes

Self-centering, Raised Face [form IBC]

This datasheet on the internet: <https://idt-gaskets.com/products/gaskets/649add7f450ff7879>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT