

# KERAM CORD

0905GE

- Aluminum silicate fiber products, reinforced with chromium steel wire, twisted round



- 15 to 20% organic carrier fibers
- Resistant to oils, fats and chemicals, except for hydrofluoric acid, phosphoric acid and strong bases
- At around 200 °C, the organic components decompose and the strength decreases
- Development of smoke or brief flare-ups at the first higher temperature exposure
- Continuous use temperature: 1100 °C
- Additional treatments/impregnation: graphite, PTFE, vermiculite, mica, silicone
- Continuous operating temperature for PTFE and silicone max. 280 °C
- Static sealing systems for furnaces, boilers, containers, etc.
- Dimensions: Ø 4–50 mm [other dimensions on request]

This datasheet on the internet: <https://idt-gaskets.com/products/textiles/62f257408ecab564e>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 201 855110 · Annaberg-Buchholz: +49 3733 5050 · München: +49 89 9918830  
Further sealing systems and technical information can be found [idt-gaskets.com](https://www.idt-gaskets.com)

Last Changed 2023-12-01