

KERAM FABRIC GASKETS

1935GE

- Aluminum silicate fiber products, reinforced with chrome steel wire and special elastomer bond 15 to 20% organic carrier fibers
- With elastic core, extremely flexible



- Very flexible, good recovery capacity. Wear-resistant, resistant to water, steam, oils, grease and most alkalis and acids. High gas tightness
- Static sealing systems for inert gas hardening systems, boilers, coal mills, flue gas ducts, fans, etc.
- Outer coatings/impregnation: graphite, PTFE, vermiculite, silicone
- Continuous operating temperature for PTFE and silicone max. 280 °C
- Forms of delivery: goods sold by the meter, endless rings, frames, special molded parts, round, rectangular, flags and special profiles
- Continuous operating temperature: 900 °C [in protective gas approx. 1100 °C]

This datasheet on the internet: <https://idt-gaskets.com/products/textiles/62f25743a387054be>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 201 855110 · Annaberg-Buchholz: +49 3733 5050 · München: +49 89 9918830
Further sealing systems and technical information can be found [idt-gaskets.com](https://www.idt-gaskets.com)

Last Changed 2023-12-01