

# PTFE/GRAPHITE-ARAMID-COMBINATION PACKING WITH LUBRICANT

2229

- Very good wear resistance yet shaft-friendly Excellent lubricating effect and heat conductivity. No gap extrusion.
- Universally applicable rotary pump packing.



## Features

Temperatur [min]	-100 °C
Temperatur [max]	260 °C
Density approx. [g/cm <sup>3</sup> ]	1.6 g/cm <sup>3</sup>
Material structure	PTFE- Aramid
Waterproofing	PTFE
Lubricant	ja
K-factor	0.9

## Fields of application

Piston pump [Vg]	5 m/s
Piston pump [p]	100 bar
Impeller pump [Vg]	25 m/s
Impeller pump [p]	25 bar
Valves [Vg]	2 m/s
Valves [p]	200 bar

This datasheet on the internet: <https://idt-gaskets.com/products/packings/629fb7aee0248ab90>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

## Applications

abrasive and sticky media	suitable
Water, Process water, Lake water	suitable
Hot water, boiler dining water	suitable
Vapors, acid gases, nitrogen	suitable
Oxygen	not suitable
Mineral oils, animal fats	suitable
Heat carrier oils, synthetic oils	limited suitability
Alcalia diluted, salt solutions	suitable
Alcalia concentrated	not suitable
Inorganic acids diluted, salt solutions	suitable
Inorganic acids concentrated	limited suitability
Solvents, other organic compounds	limited suitability
Lacques, colors [silicone -free]	not suitable

## Forms of delivery

Ready-to-install, compression-molded packing rings made to measure; as complete packing sets; sold by the meter in boxes;

1 kg	4 - 7 mm vkt.
2 kg	8 - 11 mm vkt.
3,5 kg	12 - 14 mm vkt.
5 kg	15 - 19 mm vkt.
10 kg	ab 20 mm vkt.

This datasheet on the internet: <https://idt-gaskets.com/products/packings/629fb7aee0248ab90>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT