

# RUBBER-STEEL GASKET G-ST-P/S [NBR]

0184GS10

The lens-shaped base body is also equipped with an O-ring as static sealing element.

The rubber jacketing is vulcanised firmly to the steel insert which creates a sturdy compound which can withstand even high stresses. The steel insert increases the blow-out resistance and stability of the sealing system.



## Operating data

Temperatur [min]	-25 °C
Temperatur [max]	70 °C
Pressure [max]	25 bar

## Gasket characteristics DIN 2505 V

k1 [mm]	1,6 × b <sub>d</sub>
---------	----------------------

## Gasket characteristics DIN 28090

σ <sub>VO</sub> [N/mm <sup>2</sup> ]	15
σ <sub>VU 0,1</sub> [N/mm <sup>2</sup> ]	2
m [DIN 28090]	1

## Gasket characteristics ASME

m [ASME]	2
Y [PSI]	300

## Approvals and test reports

TA Luft 2002 [VDI 24A0/2200]

W270

FDA [Food]

## Flange shapes

Plastic flange

## Notes

Proof of the required leakage rate according to TA Luft 2021 [VDI 2290] can be provided by a calculation according to DIN EN 1591-1.

This datasheet on the internet: <https://idt-gaskets.com/products/gaskets/62c2acfa17cf5f209>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scopes. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 201 855110 · Annaberg-Buchholz: +49 3733 5050 · München: +49 89 9918830  
Further sealing systems and technical information can be found [idt-gaskets.com](https://www.idt-gaskets.com)

Last Changed 2025-08-21