

## Sealmax Style 904



STYLE 904 is braided from aramid staple fibre yarn, impregnated with PTFE and a silicon-free lubricant. It is a very dense packing designed for high pressure and high speed applications. STYLE 904 is an excellent replacement for PTFE-impregnated asbestos packings and is well suited for abrasive media.

### Application Areas:

Valves, sliders, pumps, and agitators across industries where a strong and durable packing is required.

### Application Media:

Abrasive and general industrial media.

### Benefits:

Economical packing suitable for a wide variety of applications across multiple industries.

### Limitations:

Not suitable for highly concentrated acids and lyes, certain organic compounds, and alkali metals.

### OPERATING LIMITS

	ROTATING	RECEIPROCATING	STATIC
<b>Pressure</b>	20 bar	75 bar	140 bar
<b>Shaft Speed</b>	14 m/s		
<b>Density</b>	1.4 g/c m <sup>3</sup>		
<b>Temperature</b>	-100 °C to +280 °C		
<b>PH Range</b>	2 to 12		

All technical data and recommendations are given based on our experience. However, we assume no liability whatsoever. All data and values must be verified by the user, as the effectiveness of a seal can only be accurately judged by evaluating all data parameters directly on site. The stated parameters of all packing styles are approximate and may be influenced if occurring together. We suggest you to contact us in case of any special applications.



+91-89830-59377  
+91-89830-59366



admin@sealmax.net  
sales@sealmax.net  
www.sealmax.in



119/120 Raj Prabha Land Mark Industrial Estate, 1<sup>st</sup> Floor,  
Building No. 3, Bhoidapada, Vasai (East), District –  
Palghar – 401208, India